



GGX125 Grease Guardian Standard Specification

DN100 INLET (114.3mm OD pipe)
DN100 OUTLET (114.3 OD pipe)
38mm OD GREASE OUTLET pipe



GREASE GUARDIAN X STANDARD FEATURES:

- 3 Year Guarantee
- Fully Automatic Grease Removal Unit (AGRU)
- 14 gauge 304 stainless steel welded tank
- Fully sealed air tight lid
- PLC/HMI automatic controller
- Energy saving mode
- Skimming drum with automatic spray bar wash
- Automatic wash-water conditioning system
- Lift-out solids basket
- Grease Guardian World asset management

TECHNICAL DATA

Net weight (empty)	117 kgs
Gross weight (filled with water)	411 kgs
Tank capacity	294 litres
Exterior Materials	14 gauge AISI304 Stainless Steel
Interior Materials	AISI304 Stainless Steel & Acetal Components
Maximum Flow Rate	7.9 litres/s
Lift-out screen basket capacity	14 litres
Skimming Rate	10 litres per hour
Grease Retention Capacity	138+ litres
Hot wash water system operation requirements	minimum 0.75litres/s @ 3-6 bar (temp 40-60 °C)
Programming/Control	7day, 24hr multi-function PLC
Electrical Load	230VAC, 2100W, 9.1A