

Model	Tank Length (A)	Overall Length (B)	Height (C)	Width (E)	Connection Diameter (D)	Clearance needed (F)	Inlet (G)	Outlet (H)	Vent (I)	Flow Rate
NS 2	1415	1565	1363	720	114	500	1057	987	1150	- l/s
NS 4	1855	2006	1363	1015	114	500	1055	985	1170	-l/s
NS 6	2375	2565	1367	1100	125	500	1089	1020	1175	
NS 6A	-	-	-	-	-	500	-	-	-	-l/s
NS 10	2640	2840	1513	1475	168	500	1229	1147	1269	
NS 10A	-	-	-	-	-	500	-	-	-	-
NS 15	3795	3945	1730	1475	219	500	1380	1217	1430	
NS 15A	-	-	-	-	-	-	-	-	-	-

Sludge volume:100 l x flow

Grease retention: 40 l x flow

All dimensions in mm. All drawings in this brochure are guidelines and are subject to change. For full specifications and latest drawings on individual models please refer to www.greaseguardian.com or contact your local supplier.

For invert levels please contact your local supplier.

- GGNS** (Standard)
- GGNS-L** (Level Sensor)
- GGNS-W** (Standard with washdown)
- GGNS-L-W** (Level sensor and washdown)
- GGNS-L-W-P** (Wash down, pump and level sensor)